



LUMAWISE ENDURANCE N+

ANSI C136.10 COMPLIANT SHORTING AND OPEN CAPS

TE Connectivity (TE) introduces low-profile LUMAWISE Endurance N+ shorting and open caps with an integral seal gasket that provides harsh environmental protection to receptacles on roadway, street and area lighting luminaires prior to the installation of a network lighting control or when one is not required. Shorting caps are also used to designate luminaires for maintenance and to keep lights on continuously for safety. Open caps are used to temporarily disconnect service from individual luminaires while others remain energized on the same circuit.

PROVIDES A SAFER, CONVENIENT AND ECONOMICAL METHOD TO CLOSE OR OPEN THE PRIMARY CIRCUIT PATH ACROSS A NEMA TWIST LOCK RECEPTACLE ON AN OUTDOOR LIGHTING LUMINAIRE. THE LUMAWISE ENDURANCE N+ CAPS ARE ANSI C136.10 COMPLIANT, UL LISTED AND IP66 RATED.

ELECTRICAL

- Current rating: 15 A max
- Voltage rating: 0VAC – 480VAC

MECHANICAL

- Operating temperature rating: -40°C to 120°C

MATERIALS

- UV stabilized material

SPECIFICATIONS

- Product: [108-32606](#)
- Application: [114-32363](#)
- ANSI C136.10
- UL773
- IEC 61984:200 8
- IEC 60529
- IEC 62262

CERTIFICATES

- C-UL listed: E66375
- UL-EN certified: US-32907-UL

FEATURES

- Provides IP66 water ingress protection which reduces outdoor light fixture maintenance and extends operating life
- An alternative to light sensing control units
- Distinct cap shape improves visual distinction between standard photo controls and shorting caps
- IK08 high impact resistant

APPLICATIONS

- [Street and area lighting](#)
- Roadway lighting
- [Commercial outdoor lighting](#) (i.e. parking lots, car dealerships)



LUMAWISE ENDURANCE N+ SHORTING AND OPEN CAPS

PRODUCT SELECTION INFORMATION

Description	Part Number
LUMAWISE Endurance N+ Shorting Cap Assembly, Black	2361116-1
LUMAWISE Endurance N+ Shorting Open Cap, Red	2361116-2



Contact Our Product Team

We make it easy to connect with our experts and are ready to provide the support you need.

Visit [te.com/support](#) to chat with a Product Information Specialist.

[te.com/street-lighting-open-and-shorting-caps](#)

LUMAWISE, TE, TE Connectivity, TE, TE connectivity (logo) and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners.

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

© 2025 TE Connectivity. All Rights Reserved.

06-25