



TWIST SPLICE WIRE CONNECTORS

TE Connectivity's (TE) wire connectors answer the need for inexpensive, insulated electrical terminations. They can be used in almost every type of residential and commercial application where multiple wires need to be brought together for a reliable termination. TE wire connectors, which include Wire Grip, Wing Grip, Twist Grip, Ground Grip and Cap Grip connectors, are designed to meet industry standard color-coding specifications and terminate the corresponding range of wire sizes. The screw-on wire connectors contain a live-action square spring which draws wires deep into the spring for a safe, positive "grip" of the wires.

ELECTRICAL

- Rated up to 600 volt max for building wiring
- Up to 1000 volt max in lighting fixtures/luminaires and signs

MECHANICAL

- Operating Temperature: 105° C (221°F)
- Designed for copper-copper wires only

MATERIALS

- UL94V-2 flame-retardant thermoplastic

SPECIFICATIONS

- UL 486C
- CSA 22.2. NO. 188 Certified


KEY BENEFITS

- Terminate multiple wire gauges into single splice
- Tool-less twist grip termination
- Color-coded to industry standard for sizes 22-8 AWG

APPLICATIONS



Lighting
installation



Residential
building wiring



Building
equipment

FAMILY OF PRODUCTS



Wiregrip
Connectors



Winggrip



Twistgrip



Groundgrip



Capgrip

TWIST SPLICE WIRE CONNECTORS

PRODUCT SELECTION INFORMATION

	Series	Color	Wire Range (AWG)	Wire Combination		Description	TE Part Number
				Min	Max		
	Wire Grip	Gray	22 - 14	2 #22	1 #16 w/1 #18 w/1 #20	CPGI-WC-WG-GR	2299502-1
		Blue	22 - 14	2 #22	3 #16	CPGI-WC-WG-BL	2299501-1
		Orange	22 - 14	1 #18 w/1 #20	4 #16 w/1 #20	CPGI-WC-WG-OR	2299503-1
		Yellow	22 - 10	3 #20 Sol	2 #12 w/2 #14	CPGI-WC-WG-YW	2299505-1
		Red	22 - 10	3 #18	2 #10 Sol w/2 #12 Str	CPGI-WC-WG-RD	2299504-1
	Ground Grip	Green	14 - 10	2 #14	5 #12	CPGI-WC-GG-GN	2299511-1
	Twist Grip	Tan	22 - 8	3 #22 Sol	4 #12	CPGI-WC-TG-TN	2299510-1
		Gray	18 - 8	3 #14 w/1 #18	3 #10	CPGI-WC-TG-GR	2299509-1
	Wing Grip	Yellow	18 - 10	2 #18	3 #12 Sol	CPGI-WC-WNG-YW	2299508-1
		Red	18 - 8	3 #16	5 #12 Sol	CPGI-WC-WNG-RD	2299507-1
		Blue	14 - 6	2 #10 w/1 #12	3 #8 w/1 #12	CPGI-WC-WNG-BL	2299506-1
	Cap Grip	Yellow	22 - 10	4 #22	3 #12	CPGI-WC-CG-YW	2299513-1
		Red	22 - 6	3 #20	1 #8 w/3 #12 Str	CPGI-WC-CG-RD	2299512-1

Connect With Us

We make it easy to connect with our experts and are ready to provide all the support you need. Visit te.com/support to chat with a Product Information Specialist.

te.com/splices

TE Connectivity, TE, TE connectivity (logo) and EVERY CONNECTION COUNTS are trademarks owned or licensed by the TE Connectivity plc family of companies. All other logos, products and/or company names referred to herein might be trademarks of their respective owners. .

While TE has made every reasonable effort to ensure the accuracy of the information in this document, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any changes to the information contained herein without prior notice. TE Connectivity's obligations shall only be as set forth in TE Connectivity's Standard Terms and Conditions of Sale for this product and in no case will TE Connectivity be liable for any incidental, indirect, or consequential damages arising out of the sale, resale, use, or misapplication of the product. TE expressly disclaims any implied warranties with respect to the information contained herein, including, but not limited to, implied warranties of merchantability or fitness for a particular purpose. Dimensions, specifications and/or information contained herein are for reference purposes only and are subject to change without notice. Consult TE for the latest dimensions, specifications and/or information. Users of TE Connectivity products must make their own assessment as to whether the respective product is suitable for the respective desired application.

©2025 TE Connectivity. All Rights Reserved.

Published 12-25